

## Beewax Premium

Version: oct-17

*Beewax Premium* is a natural beeswax for the protection of lime-based stuccos. It prevents the absorption of water and contaminants, thus not significantly altering the substrate's permeability to gases and water vapors. Also, prevents the depigmentation of intense colors.

### PRODUCT DESCRIPTION

#### Features:

Protection of lime-based stuccos.  
Does not alter the breathability of substrates.  
Prevents the depigmentation of intense colors.  
Good workability.  
Tough and long-lasting.  
Based on natural waxed.  
Suitable for interiors and exteriors.

#### Technical properties:

Specific weight	0.9 ± 0.05 g/cm <sup>3</sup>
pH	9.5 ± 1
Nature	Natural waxed
Appearance	White liquid
Finish	Colourless

#### Yield:

30-40 m<sup>2</sup>/l (1 coat). It depends on the type and condition of the substrate. The exact consumption must be determined by the means of a sampling of the work.

#### Format:

Available in pots of 0.75 l, 4 l.

#### Storage:

Keep in original pack, closed and in a cool and dry place. Keep from freezing and avoid direct sun exposure. Unopened, it may be conserved for at least 12 months from the date of manufacture.

### APPLICATINO INSTRUCTIONS

#### Application surfaces:

Lime-based stuccos.

#### Conditions of the substrate:

The substrate must be dry, firm, well-adhered and free from any impurities that may hinder the product from setting fully.

#### Application method:

Apply one coat spreading adequately. After 30-60 minuets of application, polish with wool mop. If the mop is impregnated with wax, wait longer to polish.

#### Drying:

24 hours at 25 °C and 60% relative humidity.

#### Environmental conditions:

The work temperature (environment and support) must be between +5 °C and +32 °C. Do not apply in direct sunlight or on substrate heated by the sun.

#### Tools:

Sponge, trowel or glove with short hair.

#### Tool cleaning:

Clean tools after use with warm water.

#### Notes

Do not apply to surfaces in constant contact with water. It is not a waterproofing system.

In case of rain, let the substrate dry for at least 24 hours before applying.

It is recommended to protect the treated surface from rain and atmospheric humidity for 4 days.

To carry out decorative glazing and / or colocation of self-adhesive templates or other types of masking; dry for a week.

Should there be strict aesthetic requirements, it is recommended to perform prior tests.

The parts that are not going to be treated must be protected (glass, wood, etc.).

Do not mix with other products or specific properties may change.

### ADDITIONAL INFORMATION

#### Usage warnings:

None in particular for normal use and people who do not have special pathologies. Alkaline product, protect skin and eyes especially. Apply with good ventilation, do not inhale product. Keep out of reach of children.

### Waste management:

According to local legal provisions. The pots are made of recycled polypropylene. Help protect the environment, do not throw waste through the drain and use the nearest recycling centre.

### Responsible gesture:

Minimize the product waste by estimating the amount you will need. Recover the unused product to give it a new use, keep it under the Storage section.

### Safety information:

For information regarding safety, physical, ecological and toxicological information see the latest version of the product's Material Safety Data Sheet.

### Technical substrate:

For further information, please contact with local distributor or manufacture ([technicalsupport@graphenstone.com](mailto:technicalsupport@graphenstone.com)).

The information provided is given in good faith, based on current knowledge and IEdiSA's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of IEdiSA. The Technical Specifications sheet is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. IEdiSA reserves the right to modifications that improve the product or its application. This version invalidates previous ones.